



# Fabric Specification Sheet

## Preliminary

<b>Style:</b>	<b><u>Apagòn Style I</u></b>	
<b>Construction:</b>	3 ply (50% vinyl, 41.8% fiberglass, 8.1% Proprietary Coating) (Each vinyl is equal thickness and weight)	
<b>Surface Texture:</b>	Back side Laminated with Coated front side	
<b>Colors Available:</b>	Refer to Product Index	
<b>Thread Count:</b>	64 threads per square inch (25 per square centimeter)	
<b>Available Widths:</b>	98" (249 cm) Other widths Available upon request	
<b>Roll Lengths:</b>	30-yard standard (27 Meters)	
<b>Shipping:</b>	Rolls shipped on 3" (7.62 cm) ID paper	
<b>Weight Per Sq. Yard:</b>	16 ounces (542.4 grams/m <sup>2</sup> )	(+ or - 2.0) (+ or - 68)
<b>Thickness:</b>	17.9 mil (.455 millimeters)	(+ or - 2.0) (+ or - .05)
<b>Tear Strength:</b>	Warp 22.04 Lbs/In	Fill 17.84 Lbs/In
<b>Breaking Strength:</b>	Warp 449.46 Lbs/In	Fill 264.29 Lbs/In
<b>Washability:</b>	Material may be dusted with a damp cloth. When scrubbing is necessary, warm water, mild detergents, and gentle rubbing are recommended.	
<b>Opacity: Visual check</b>	Blackout	
<b>Flammability:</b>	National Fire Protection Association Standard 701 Test Method one 2019 edition	
<b>Other Tests Passed:</b>	ASTM D3335 85a Lead Testing Pending- ASTM G21 testing	

7/11/2019

MAILING ADDRESS  
P.O. Box 1017  
Warsaw, IN 46581

STREET ADDRESS  
102 Enterprise Drive  
Warsaw, IN 46580

PHONE  
(574) 269-1280

FAX  
(574) 269-7747

E-MAIL  
Mail@indianacoatedfabrics.com

WEBSITE  
www.indianacoatedfabrics.com