



Fabric Specification Sheet

Preliminary

Style:	<u>Apagòn Style IV</u>
Construction:	3 ply (49.1% vinyl, 33.4% fiberglass, 17.37% Proprietary Coating) (Each vinyl is equal thickness and weight)
Surface Texture:	Back side Laminated with Coated front side
Colors Available:	Refer to Product Index
Thread Count:	59 threads per square inch (23 per square centimeter)
Available Widths:	72" (182.8 cm) Other widths Available upon request
Roll Lengths:	30-yard standard (27 Meters)
Shipping:	Rolls shipped on 3" (7.62 cm) ID paper
Weight Per Sq. Yard:	12.2 ounces (+ or - 2.0) (406.8 grams/m ²) (+ or - 68)
Thickness:	mil (+ or - 2.0) (.31 millimeters) (+ or - .05)
Tear Strength:	Warp 15.8 Lbs/In Fill 10.98 Lbs/In
Breaking Strength:	Warp 289.74 Lbs/In Fill 327.81 Lbs/In
Washability:	Material may be dusted with a damp cloth. When scrubbing is necessary, warm water, mild detergents, and gentle rubbing are recommended.
Opacity: Visual check	Blackout
Flammability:	National Fire Protection Association Standard 701 Test Method one 2019 edition
Other Tests Passed:	ASTM D3335 85a Lead Testing Pending- ASTM G21 Testing

7/11/2019

MAILING ADDRESS
P.O. Box 1017
Warsaw, IN 46581

STREET ADDRESS
102 Enterprise Drive
Warsaw, IN 46580

PHONE
(574) 269-1280

FAX
(574) 269-7747

E-MAIL
Mail@indianacoatedfabrics.com

WEBSITE
www.indianacoatedfabrics.com