

SUN ○ PROTECTION

SHADE 1134


Number	Colour	Width mm			Light Properties			Solar Properties			Light Fastness	Gtot - value	FC - value
		89	127	3000	R	T	A	R	T	A			
1089	white	✓	✓	✓	56%	16%	28%	50%	20%	30%	6-7	>0,45	>0,80
2368	sand	✓	✓	✓	37%	9%	54%	34%	11%	55%	6-7	>0,45	>0,80
9169	shell	✓	✓	✓	42%	12%	46%	37%	15%	48%	6-7	>0,45	>0,80
2367	golden brown	✓	✓	✓	21%	8%	71%	17%	10%	73%	6-7	>0,45	>0,80
9223	silver-iron	✓	✓	✓	22%	7%	71%	22%	11%	67%	6-7	>0,45	>0,80
9167	shine black	✓	✓	✓	19%	7%	74%	16%	9%	75%	6-7	>0,45	>0,80
8178	mahagony	✓	✓	✓	25%	11%	64%	23%	14%	63%	6-7	>0,45	>0,80

All printed colours and textures only provide orientation and are not reference pattern.

Usable for	Roller / Vertical / Pleated / Panel Track	Weight	160 g/m2
Colour Range	7	Thickness	0,35 mm
Composition	100 % PES	Moisture proofed	yes
Width	89 / 127 / 3000 mm	PVC free	yes
Cutting Process	hot	Halogen free	yes
Processing Direction	warp & weft	OekoTex	yes



suitable for workstations



B semi-transparent



Standard 100 by Oeko-Tex®

R = Reflection, T = Transmission, A = Absorption • All light & solar properties have been tested internally or externally. • Gtot: measure total solar energy that passes through the glazing system and the fabric • Fc-value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g • All technical properties are subjected to production-related deviations. All fabrics are in line with the REACh regulation.