

SUN ○ PROTECTION

REVIVAL 1162

Number	Colour	Width mm			Light Properties			Solar Properties			Light Fastness	Gtot - value	FC - value
		89	127	2300	R	T	A	R	T	A			
9196	dust grey	✓	✓	✓	48%	34%	18%	45%	37%	18%	6-7	>0,55	>0,70
2323	sand	✓	✓	✓	37%	31%	32%	32%	35%	33%	6-7	>0,55	>0,70
9190	rock	✓	✓	✓	29%	27%	44%	25%	32%	43%	6-7	>0,55	>0,70
9197	iron	✓	✓	✓	11%	21%	68%	10%	25%	65%	6-7	>0,55	>0,70


All printed colours and textures only provide orientation and are not reference pattern.

Usable for Roller / Vertical / Panel Track
 Colour Range 4
 Composition 100 % PES (recycled)
 Width 89 / 127 / 2300 mm
 Cutting Process hot
 Processing Direction warp

Weight 150 g/m²
 Thickness 0,35 mm
 Moisture proofed yes
 PVC free yes
 Halogen free yes
 OekoTex yes



Recycled



B semi-transparent



Standard 100 by Oeko-Tex®



by Gerhard van Clewe GmbH & Co.KG

R = Reflection, T = Transmission, A = Absorption • All light & solar properties have been tested internally or externally. • Gtot: measure total solar energy that passes through the glazing system and the fabric • Fc-value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g. • All technical properties are subjected to production-related deviations. All fabrics are in line with the REACh regulation • All substances, mentioned in the icons, are not used acc. to our recipe. • Finished by a STeP certified company.